



COMPLIES WITH
LEAD-FREE
PLUMBING LAWS



Features & Benefits

- Body: Lead Free Brass
- Connection: Press-Fit x Press-Fit
- Sizes: 1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 2 1/2", 3", 4"
- Pressure Rating: 200 CWP
- Maximum Temperature: 180° F
- Port: Full
- Seal: PTFE
- Packing Description: PTFE - Adjustable
- Blow-Out Proof Stem
- 2-Piece Body
- (1/2" - 2") Press Indicator
- (1/2"-1") Solid Ball
- Used with Ridgid, Milwaukee, Dewalt, & Rothenberger tools
- For Domestic Hot & Cold Drinking Water, Chilled HVAC Systems, and Isolation Applications
- Positive Shut-Off
- ANSI/NSF 372 (Lead-Free Drinking Water Laws)
- ANSI/NSF 61 IAMPO/ANSI Z1157



LEAD FREE BALL VALVES: LESS THAN 0.25% LEAD Conforms with AB1953 and Safe Drinking Water Act

SIZE	DESCRIPTION	UPC	BOX QUANTITY	LIST PRICE
G111 (Press Fit x Press Fit, Full Port)				
1/2"	Lead Free Brass Ball Valve Press-Fit	611918107783	50	\$10.49
3/4"	Lead Free Brass Ball Valve Press-Fit	611918107790	30	\$18.36
1"	Lead Free Brass Ball Valve Press-Fit	611918107806	18	\$26.86
1 1/4"	Lead Free Brass Ball Valve Press-Fit	611918107813	12	\$39.94
1 1/2"	Lead Free Brass Ball Valve Press-Fit	611918107820	10	\$57.58
2"	Lead Free Brass Ball Valve Press-Fit	611918107837	8	\$100.83
2 1/2"	Lead Free Brass Ball Valve Press-Fit	611918107844	1	\$265.80
3"	Lead Free Brass Ball Valve Press-Fit	611918107851	1	\$385.51
4"	Lead Free Brass Ball Valve Press-Fit	611918107868	1	\$655.20

