



COMPLIES WITH
LEAD-FREE
PLUMBING LAWS



Features & Benefits

- Body: Lead Free Brass
- Connection: Press-Fit x Press-Fit
- Sizes: 1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 2 1/2", 3", 4"
- Pressure Rating: 200 CWP
- Maximum Temperature: 180° F
- Port: Full
- Seal: PTFE
- Packing Description: PTFE - Adjustable
- Blow-Out Proof Stem
- 2-Piece Body
- (1/2" - 2") Press Indicator
- (1/2"-1") Solid Ball
- Used with Ridgid, Milwaukee, Dewalt, & Rothenberger tools
- For Domestic Hot & Cold Drinking Water, Chilled HVAC Systems, and Isolation Applications
- Positive Shut-Off
- ANSI/NSF 372 (Lead-Free Drinking Water Laws)
- ANSI/NSF 61 IAMPO/ANSI Z1157

**NEW
PRICING!**

The American Valve G111 lead free press-fit brass ball valve

1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
\$13.74	\$19.10	\$32.31	\$47.33	\$65.76	\$108.15	\$197.48	\$299.70	\$500.47

